

Exact determination of the volume of an inclusion in a body having constant shear modulus

Andrew E Thaler and Graeme W Milton

Department of Mathematics, University of Utah, Salt Lake City, UT 84112, USA

E-mail: thaler@math.utah.edu, milton@math.utah.edu

Abstract. We derive an exact formula for the volume fraction of an inclusion in a body when the inclusion and the body are linearly elastic materials with the same shear modulus. Our formula depends on an appropriate measurement of the displacement and traction around the boundary of the body. In particular, the boundary conditions around the boundary of the body must be such that they mimic the body being placed in an infinite medium with an appropriate displacement applied at infinity.

AMS classification scheme numbers: 74B05, 35Q74

Keywords: volume fraction, Dirichlet-to-Neumann map, artificial boundary conditions

Submitted to: *Inverse Problems*

1. Introduction

A fundamental and interesting problem in the study of materials is the estimation of the volume fraction occupied by an inclusion D in a body Ω . Although the volume fraction could be determined by weighing the body, the densities of the materials may be close or unknown or weighing the body may be impractical. Because of this, many methods have been developed which utilize measurements of certain fields around $\partial\Omega$ to derive bounds on the volume fraction $|D|/|\Omega|$, where $|U|$ is the Lebesgue measure of the set U [1–23]. In this paper, we show that under certain circumstances the volume fraction $|D|/|\Omega|$ can be computed exactly from a single appropriate boundary measurement around $\partial\Omega$. We note that many of the results in the literature (and our results in this paper) can also be applied when Ω contains a two-phase composite with microstructure much smaller than the dimensions of Ω .

We consider an inclusion D in a body Ω (or a two-phase composite inside Ω), where Ω is a subset of $\mathbb{R}^d$ ($d = 2$ or 3). We assume that the inclusion and body are filled with linearly elastic materials with the same shear modulus μ and Lamé moduli λ_1 and λ_2 , respectively. Our goal is to determine the volume fraction occupied by the inclusion, namely $|D|/|\Omega|$, in terms of a measurement of the displacement and traction around $\partial\Omega$. The boundary conditions around $\partial\Omega$ are taken to be such that they mimic the body Ω being placed in an infinite medium with a suitable field at infinity. The starting point for our result is based on an exact relation due to Hill [24], which we now describe.

One of the most important problems in the study of composite materials is the determination of effective moduli given information about the local moduli — see, e.g., the work by Hashin [25] and the book by Milton [26] (Chapters 1 and 2 in particular). In general, it is extremely difficult (if not impossible) to determine effective parameters exactly, even if the microgeometry of the composite is known and relatively uncomplicated. However, many useful approximation techniques and bounds on effective properties of composites have been derived in the literature — see the book by Milton [26] and the references therein for a vast collection of such results. Surprisingly, there are several circumstances in which exact links between effective moduli (or exact formulas for the moduli themselves) can be derived regardless of the complexity of the microstructure; such links are known as *exact relations*.

Exact relations exist for a variety of problems including elasticity and coupled problems such as thermoelasticity, thermoelectricity, piezoelectricity, thermo-piezoelectricity, and others — see the review articles by Dvorak and Benveniste [27] and Milton [28], the work by Grabovsky, Milton, and Sage [29], the works by Hegg [30, 31], and the references therein for summaries of numerous previous and current results on exact relations.

Perhaps even more surprising than the existence of exact relations is the existence of a general mathematical theory of exact relations, developed by Grabovsky, Milton, and Sage [29, 32–35], that allows us to determine all of the above mentioned exact relations and many more. For example, Hegg applied this general theory to the study

of fiber-reinforced elastic composites [30, 31].

Rather than study the general theory, we focus on a specific exact relation derived by Hill [24, 36]. In particular, Hill considered a two-phase composite material consisting of two homogeneous and isotropic phases with the same shear modulus μ but different Lamé moduli λ_1 and λ_2 . Hill proved that such a composite is macroscopically elastically isotropic with shear modulus μ and effective Lamé modulus λ_* ; he also derived an exact formula for λ_* that holds regardless of the complexity of the microgeometry. His derivation of this formula [24, 36] provides the starting point of our work in this paper.

We begin by assuming that the body Ω is embedded in an infinite medium with Lamé modulus λ_E and shear modulus μ (we take $\lambda_E = \lambda_2$ for simplicity) and that a displacement $\mathbf{u} = \nabla g$ is applied at infinity. Using a method similar to Hill's derivation of λ_* , we derive a formula for $|D|/|\Omega|$ in terms of a measurement of the displacement around $\partial\Omega$, the (known) parameters λ_1 , λ_2 , and μ , and the (known) function g . In order to make the situation more practical, we derive a certain nonlocal boundary condition that can be applied to $\partial\Omega$ that forces the body to behave as if it actually were embedded in an infinite medium with Lamé modulus λ_2 , shear modulus μ , and an applied displacement $\mathbf{u} = \nabla g$ at infinity. This nonlocal boundary condition couples the measurements of the traction and displacement around $\partial\Omega$.

Nonlocal boundary conditions which mimic infinite media similar to the one mentioned above are common tools used in the numerical solution of PDEs (and ODEs) in infinite domains — see, e.g., the review article by Givoli [37] and references therein for examples specific to scattering problems, the work by Han and Wu on the Laplace equation [38] and elasticity equations [39], the work by Lee, Caflisch, and Lee on the elasticity equations [40], and references therein.

As discussed above, our formula for the volume fraction $|D|/|\Omega|$ holds as long as the body Ω is embedded in an infinite medium with an applied displacement $\mathbf{u} = \nabla g$ at infinity. In Section 4 we derive a nonlocal boundary condition such that if this boundary condition is applied to $\partial\Omega$ the solution inside Ω will be equal to the restriction to Ω of the solution to the infinite problem. Our boundary condition depends on the function g and on the exterior Dirichlet-to-Neumann map on $\partial\Omega$ (which, when the body Ω is absent, maps the displacement on $\partial\Omega$ to the traction on $\partial\Omega$ when no fields are applied at infinity). Thus it is closely related to the boundary condition of Han and Wu [38, 39] and Bonnaillie-Noël, Dambrine, Hérau, and Vial [41] — see Section 4 for complete details.

The rest of this paper is organized as follows. In Section 2 we briefly review the linear elasticity equations and relevant results from homogenization theory. Next, in Section 3 we derive a formula that gives the exact volume fraction of an inclusion in a body when the inclusion and the body have the same shear modulus μ and the body is embedded in an infinite medium with shear modulus μ . We discuss the nonlocal boundary condition relevant to our problem in Section 4 so we can focus on a (more realistic) finite domain. Finally, in Section 5 we present the analytical expression of the nonlocal boundary condition in the particular case when Ω is a disk in $\mathbb{R}^2$ — this expression was first derived by Han and Wu [38, 39]. A complete derivation of our

nonlocal boundary condition is given in work by one of the authors of this paper [23].

2. Elasticity

We begin by recalling a few definitions from Hegg's work [30, 31]. Let $d = 2$ or 3 be the dimension under consideration; then $\text{Sym}(\mathbb{R}^d)$ is the set of all symmetric linear mappings from $\mathbb{R}^d$ to itself, i.e.,

$$\text{Sym}(\mathbb{R}^d) \equiv \{\mathbf{B} \in \mathbb{R}^d \otimes \mathbb{R}^d \mid \mathbf{B} = \mathbf{B}^T\}.$$

Similarly, the set $\text{Sym}(\text{Sym}(\mathbb{R}^d))$ is defined as the set of symmetric linear mappings from $\text{Sym}(\mathbb{R}^d)$ to itself. If $\mathbb{A} \in \text{Sym}(\text{Sym}(\mathbb{R}^d))$ and $\mathbf{B} \in \text{Sym}(\mathbb{R}^d)$, then $\mathbb{A} : \mathbf{B} \in \text{Sym}(\mathbb{R}^d)$ with elements

$$(\mathbb{A} : \mathbf{B})_{ij} = A_{ijkl} B_{kl}, \quad (1)$$

where here and throughout the paper we use the Einstein summation convention that repeated indices are summed from 1 to d .

Consider a linearly elastic body which is either a periodic composite material with unit cell $\Omega \subset \mathbb{R}^d$ or which occupies an open, bounded set $\Omega \subset \mathbb{R}^d$. Let $\mathbf{u}(\mathbf{x})$, $\boldsymbol{\varepsilon}(\mathbf{x})$, and $\boldsymbol{\sigma}(\mathbf{x})$ denote the displacement, linearized strain tensor, and Cauchy stress tensor, respectively, at the point $\mathbf{x} \in \Omega$. Then $\mathbf{u} \in \mathbb{R}^d$ while $\boldsymbol{\varepsilon}$ and $\boldsymbol{\sigma}$ belong to $\text{Sym}(\mathbb{R}^d)$. By Hooke's Law, the stress and strain tensor are related through the linear constitutive relation

$$\boldsymbol{\sigma}(\mathbf{x}) = \mathbb{C}(\mathbf{x}) : \boldsymbol{\varepsilon}(\mathbf{x}), \quad (2)$$

where $\mathbb{C} \in \text{Sym}(\text{Sym}(\mathbb{R}^d))$ is the elasticity (or stiffness) tensor. We assume $\mathbb{C}$ is elliptic for all $\mathbf{x} \in \Omega$, i.e., there are positive constants a and b such that

$$\mathbf{B} : [\mathbb{C}(\mathbf{x}) : \mathbf{B}'] \leq a \|\mathbf{B}\| \|\mathbf{B}'\| \quad \text{and} \quad \mathbf{B} : [\mathbb{C}(\mathbf{x}) : \mathbf{B}] \geq b \|\mathbf{B}\|^2$$

for all $\mathbf{B}, \mathbf{B}' \in \text{Sym}(\mathbb{R}^d)$ and where $\|\mathbf{B}\|^2 = \frac{1}{2}(\mathbf{B} : \mathbf{B})$. If there are no body forces present, then at equilibrium the elasticity equations are

$$\nabla \cdot \boldsymbol{\sigma}(\mathbf{x}) = 0, \quad \boldsymbol{\varepsilon}(\mathbf{x}) = \frac{1}{2} [\nabla \mathbf{u}(\mathbf{x}) + \nabla \mathbf{u}(\mathbf{x})^T], \quad \text{and} \quad \boldsymbol{\varepsilon}(\mathbf{x}) = \mathbb{C}(\mathbf{x}) : \boldsymbol{\sigma}(\mathbf{x}); \quad (3)$$

see, e.g., Chapter 2 of the book by Milton [26].

If the composite is locally isotropic, the local elasticity tensor takes the form

$$\mathbb{C}(\mathbf{x}) = \lambda(\mathbf{x}) \mathbf{I} \otimes \mathbf{I} + 2\mu(\mathbf{x}) \mathbb{I},$$

where λ is the Lamé modulus, μ is the shear modulus, $\mathbf{I} \in \text{Sym}(\mathbb{R}^d)$ is the second-order identity tensor with elements $I_{ij} = \delta_{ij}$ (where δ_{ij} is the Kronecker delta which is 1 if $i = j$ and 0 otherwise), and $\mathbb{I} \in \text{Sym}(\text{Sym}(\mathbb{R}^d))$ is the fourth-order identity tensor which maps an element in $\text{Sym}(\mathbb{R}^d)$ to itself under contraction [26]. In this case, Hooke's Law (2) reduces to

$$\mathbf{S}\mathbf{u}(\mathbf{x}) \equiv \boldsymbol{\sigma}(\mathbf{x}) = \lambda(\mathbf{x}) \text{Tr}[\boldsymbol{\varepsilon}(\mathbf{x})] \mathbf{I} + 2\mu(\mathbf{x}) \boldsymbol{\varepsilon}(\mathbf{x}) \quad (4)$$

$$= \lambda(\mathbf{x}) [\nabla \cdot \mathbf{u}(\mathbf{x})] \mathbf{I} + \mu(\mathbf{x}) [\nabla \mathbf{u}(\mathbf{x}) + \nabla \mathbf{u}(\mathbf{x})^T], \quad (5)$$

where $\mathcal{S} : \mathbb{R}^d \rightarrow \text{Sym}(\mathbb{R}^d)$ is the linear stress operator that maps the displacement $\mathbf{u}$ to the stress $\boldsymbol{\sigma}$ (note that $\mathcal{S}$ itself depends on $\mathbf{x}$ through $\lambda(\mathbf{x})$ and $\mu(\mathbf{x})$).

The bulk modulus, Young's modulus, and the Poisson ratio are related to λ and μ by

$$\kappa = \lambda + \frac{2\mu}{d}, \quad E = \frac{2\mu(d\lambda + 2\mu)}{(d-1)\lambda + 2\mu}, \quad \text{and} \quad \nu = \frac{\lambda}{(d-1)\lambda + 2\mu},$$

respectively [26]. Throughout this paper we assume [42]

$$\mu(\mathbf{x}) > 0 \quad \text{and} \quad d\lambda(\mathbf{x}) + 2\mu(\mathbf{x}) > 0. \quad (6)$$

We define the average of a tensor-valued function $\mathbf{M}(\mathbf{x})$ over a set $\mathcal{M} \subset \mathbb{R}^d$ by

$$\langle \mathbf{M} \rangle_{\mathcal{M}} \equiv \frac{1}{|\mathcal{M}|} \int_{\mathcal{M}} \mathbf{M}(\mathbf{x}) \, d\mathbf{x}, \quad (7)$$

where $|\mathcal{M}|$ denotes the Lebesgue measure of the set $\mathcal{M}$. The effective elasticity tensor $\mathbb{C}_*$ is defined at sample points $\mathbf{x} \in \Omega$ through

$$\langle \boldsymbol{\sigma} \rangle_{\Omega'(\mathbf{x})} = \mathbb{C}_*(\mathbf{x}) \langle \boldsymbol{\varepsilon} \rangle_{\Omega'(\mathbf{x})}, \quad (8)$$

where $\Omega'(\mathbf{x})$ is a suitably chosen representative volume element centered at $\mathbf{x}$.

3. Exact Volume Fraction

In this section we derive a formula that gives the exact volume fraction occupied by an inclusion in a body, where our formula depends on a boundary measurement of the displacement. Let D and Ω be open, bounded sets in $\mathbb{R}^d$ with $D \subset \Omega$. Suppose $\mathbb{R}^d$ is filled with a linearly elastic, locally isotropic material with constant shear modulus μ and Lamé modulus

$$\lambda(\mathbf{x}) = \lambda_1 \chi_D(\mathbf{x}) + \lambda_2 \chi_{\mathbb{R}^d \setminus \overline{D}}(\mathbf{x}). \quad (9)$$

Since the material is locally isotropic, the elasticity tensor is

$$\mathbb{C}(\mathbf{x}) = \lambda(\mathbf{x}) \mathbf{I} \otimes \mathbf{I} + 2\mu \mathbb{I}. \quad (10)$$

We can write $\mathcal{S}\mathbf{u}(\mathbf{x})$ from (5) as

$$\mathcal{S}\mathbf{u}(\mathbf{x}) = \begin{cases} \mathcal{S}_1 \mathbf{u}(\mathbf{x}) \equiv \lambda_1 [\nabla \cdot \mathbf{u}(\mathbf{x})] \mathbf{I} + \mu [\nabla \mathbf{u}(\mathbf{x}) + \nabla \mathbf{u}(\mathbf{x})^T] & \text{for } \mathbf{x} \in D, \\ \mathcal{S}_2 \mathbf{u}(\mathbf{x}) \equiv \lambda_2 [\nabla \cdot \mathbf{u}(\mathbf{x})] \mathbf{I} + \mu [\nabla \mathbf{u}(\mathbf{x}) + \nabla \mathbf{u}(\mathbf{x})^T] & \text{for } \mathbf{x} \in \mathbb{R}^d \setminus \overline{D}. \end{cases} \quad (11)$$

According to the elasticity equations in (3), the displacement $\mathbf{u}$ satisfies

$$\begin{cases} \mathcal{L}_1 \mathbf{u} = 0 & \text{in } D, \\ \mathcal{L}_2 \mathbf{u} = 0 & \text{in } \mathbb{R}^d \setminus \overline{D}, \\ \mathbf{u}, \boldsymbol{\sigma} \cdot \mathbf{n}_D = (\mathcal{S}\mathbf{u}) \cdot \mathbf{n}_D & \text{continuous across } \partial D, \\ \mathbf{u} - \mathbf{f} = \mathcal{O}(|\mathbf{x}|^{1-d}) & \text{as } |\mathbf{x}| \rightarrow \infty, \end{cases} \quad (12)$$

where $\mathcal{L}_j \mathbf{u} = -(\lambda_j + \mu) \nabla (\nabla \cdot \mathbf{u}) - \mu \Delta \mathbf{u}$ (for $j = 1, 2$) is the Lamé operator, $\mathbf{n}_D$ is the outward unit normal vector to ∂D , $\boldsymbol{\sigma} = \mathcal{S}\mathbf{u}$ is the stress tensor associated with $\mathbf{u}$, and the function $\mathbf{f} = \nabla g$ is given and satisfies $\mathcal{L}_2 \mathbf{f} = \mathcal{L}_2 \nabla g = 0$ for all $\mathbf{x} \in \mathbb{R}^d$. To avoid

possible technical complications we assume that g is at least three times continuously differentiable in $\mathbb{R}^d$. The function $\mathbf{f}$ represents the “displacement at infinity”; perhaps the simplest example of such a function is $\mathbf{f}(\mathbf{x}) = \mathbf{x}$, in which case $g = \frac{1}{2}(\mathbf{x} \cdot \mathbf{x}) + \text{constant}$. As shown in Chapters 9 and 10 of the book by Ammari and Kang [42], there exists a unique solution $\mathbf{u}$ to (12) if D is a Lipschitz domain.

Following Hill’s work [24, 36], we assume there is a continuously differentiable potential ϕ such that $\mathbf{u} = \nabla\phi$. In particular, we assume ϕ and $\nabla\phi$ are continuous across ∂D (by (12), $\mathbf{u} = \nabla\phi$ must be continuous across ∂D). Also, for $i, j = 1, \dots, d$, we have

$$(\nabla\nabla\phi)_{ij} = \frac{\partial^2\phi}{\partial x_i \partial x_j}; \quad (13)$$

note that the matrix $\nabla\nabla\phi$ is symmetric in each phase. We only assume that ϕ and $\nabla\phi$ are continuous across ∂D (indeed, as shown by Hill [43], $\partial^2\phi/\partial x_i \partial x_j$ is discontinuous across ∂D). Then from (3) we have

$$\boldsymbol{\varepsilon} = \frac{1}{2}(\nabla\mathbf{u} + \nabla\mathbf{u}^T) = \frac{1}{2}[\nabla\nabla\phi + (\nabla\nabla\phi)^T] = \nabla\nabla\phi. \quad (14)$$

From (13) and (14) we have $\text{Tr}(\boldsymbol{\varepsilon}) = \text{Tr}(\nabla\nabla\phi) = \Delta\phi$, where $\Delta = \nabla \cdot \nabla = \partial^2/\partial x_i \partial x_i$ is the Laplacian. Then (4) and (14) imply

$$\boldsymbol{\sigma}(\mathbf{x}) = \mathbb{C}(\mathbf{x}) : \boldsymbol{\varepsilon}(\mathbf{x}) = \lambda(\mathbf{x})\Delta\phi\mathbf{I} + 2\mu\nabla\nabla\phi. \quad (15)$$

Finally, for $j = 1$ and $j = 2$ we have

$$\begin{aligned} \mathcal{L}_j\mathbf{u} &= -(\lambda_j + \mu)\nabla(\nabla \cdot \nabla\phi) - \mu\Delta(\nabla\phi) \\ &= -(\lambda_j + \mu)\nabla(\Delta\phi) - \mu\nabla(\Delta\phi) \\ &= -(\lambda_j + 2\mu)\nabla(\Delta\phi). \end{aligned} \quad (16)$$

By assumption, we have

$$0 = \mathcal{L}_2\mathbf{f} = -(\lambda_2 + 2\mu)\nabla(\Delta g)$$

for all $x \in \mathbb{R}^d$, so $\nabla(\Delta g) = 0$ for all $\mathbf{x} \in \mathbb{R}^d$. Then we must have $\Delta g = C_g \neq 0$ for all $\mathbf{x} \in \mathbb{R}^d$, where C_g is a constant. (The constant C_g is known since g is known; we will see later why we must take $C_g \neq 0$.) Thus the function g must be chosen so that $g = (C_g/2)\mathbf{x} \cdot \mathbf{x} + g_h$, where g_h is harmonic in $\mathbb{R}^d$. This implies that g is infinitely differentiable in $\mathbb{R}^d$ [44].

Recalling that $\mathbf{u} = \nabla\phi$ and $\mathbf{f} = \nabla g$, we see that (16) implies that (12) becomes

$$\begin{cases} \nabla(\Delta\phi) = 0 & \text{in } D \text{ and } \mathbb{R}^d \setminus \overline{D}, \\ \nabla\phi, \boldsymbol{\sigma} \cdot \mathbf{n}_D = (\mathcal{S}\nabla\phi) \cdot \mathbf{n}_D & \text{continuous across } \partial D, \\ \nabla\phi - \nabla g = \mathcal{O}(|x|^{1-d}) & \text{as } |\mathbf{x}| \rightarrow \infty, \end{cases} \quad (17)$$

where $\boldsymbol{\sigma} = \mathcal{S}\nabla\phi$ is given in (15).

3.1. Behavior of $\Delta\phi$

In this section we study the behavior of $\Delta\phi$. Recall that we assume ϕ to be at least continuously differentiable in $\mathbb{R}^d$; in particular, this implies that ϕ and $\mathbf{u} = \nabla\phi$ are continuous across ∂D (see (17)). If $\mathbf{f}$ is smooth the solution $\mathbf{u}$ to (12) is smooth in $\mathbb{R}^d \setminus \overline{D}$ and in D [42, equation (10.2)] (although it is only continuous across ∂D).

Since ϕ is smooth in D and $\mathbb{R}^d \setminus \overline{D}$, (17) implies that $\Delta\phi$ is constant in each phase, i.e.,

$$\Delta\phi = \begin{cases} C_1 & \text{in } D, \\ C_2 & \text{in } \mathbb{R}^d \setminus \overline{D}. \end{cases} \quad (18)$$

Recall from (3) that $\nabla \cdot \boldsymbol{\sigma} = 0$ in $\mathbb{R}^d$. By (15), this becomes

$$\begin{aligned} 0 &= \nabla \cdot \boldsymbol{\sigma}(\mathbf{x}) \\ &= \nabla \cdot [\lambda(\mathbf{x})\Delta\phi(\mathbf{x})\mathbf{I} + 2\mu\nabla\nabla\phi(\mathbf{x})] \\ &= \nabla [\lambda(\mathbf{x})\Delta\phi(\mathbf{x})] + 2\mu\nabla \cdot \nabla\nabla\phi(\mathbf{x}) \\ &= \nabla [\lambda(\mathbf{x})\Delta\phi(\mathbf{x})] + 2\mu\Delta [\nabla\phi(\mathbf{x})] \\ &= \nabla \{[\lambda(\mathbf{x}) + 2\mu]\Delta\phi(\mathbf{x})\}. \end{aligned} \quad (19)$$

This implies that

$$[\lambda(\mathbf{x}) + 2\mu]\Delta\phi(\mathbf{x}) = C \quad \Leftrightarrow \quad \Delta\phi(\mathbf{x}) = \frac{C}{\lambda(\mathbf{x}) + 2\mu} \quad (20)$$

almost everywhere in $\mathbb{R}^d$, where C is a constant [26, Chapter 5]. Then, due to (18) and (20), we have

$$\Delta\phi = \begin{cases} C_1 = \frac{C}{\lambda_1 + 2\mu} & \text{in } D, \\ C_2 = \frac{C}{\lambda_2 + 2\mu} & \text{in } \mathbb{R}^d \setminus \overline{D}. \end{cases} \quad (21)$$

By (17), we have $\nabla\phi - \nabla g \rightarrow 0$ as $|\mathbf{x}| \rightarrow \infty$; thus $\Delta\phi - \Delta g \rightarrow 0$ as $|\mathbf{x}| \rightarrow \infty$. Since $\Delta g = C_g$, $\Delta\phi \rightarrow C_g$ as $|\mathbf{x}| \rightarrow \infty$. Since $\lambda(\mathbf{x}) = \lambda_2$ for large enough $\mathbf{x}$, we take the limit of (20) and find that

$$C = \lim_{|\mathbf{x}| \rightarrow \infty} \{[\lambda(\mathbf{x}) + 2\mu]\Delta\phi(\mathbf{x})\} = (\lambda_2 + 2\mu)C_g. \quad (22)$$

Finally, (9), (20), and (22) imply that

$$\Delta\phi = \nabla \cdot \mathbf{u} = \begin{cases} C_1 = \left(\frac{\lambda_2 + 2\mu}{\lambda_1 + 2\mu}\right) C_g & \text{in } D, \\ C_g & \text{in } \mathbb{R}^d \setminus \overline{D}. \end{cases} \quad (23)$$

3.2. Main Result

The divergence theorem and (23) imply

$$\int_{\partial\Omega} \mathbf{u} \cdot \mathbf{n}_\Omega \, dS = \int_D \nabla \cdot \mathbf{u} \, d\mathbf{x} + \int_{\Omega \setminus \overline{D}} \nabla \cdot \mathbf{u} \, d\mathbf{x} = (C_1 - C_2)|D| + C_2|\Omega|.$$

Therefore the volume fraction of the inclusion is given by the formula

$$\frac{|D|}{|\Omega|} = \frac{1}{C_1 - C_2} \left(\frac{1}{|\Omega|} \int_{\partial\Omega} \mathbf{u} \cdot \mathbf{n}_\Omega \, dS - C_2 \right), \quad (24)$$

where C_1 and C_2 are related to C_g by (23), respectively. Since we are assuming we have complete knowledge of $\mathbf{u}$ around $\partial\Omega$ from our measurement, and since $C_g = \Delta g$ is given, (24) allows us to exactly determine $|D|/|\Omega|$. Note also that we must take $C_g \neq 0$. If $C_g = 0$, then (23) implies that $C_1 = C_2 = 0$, which makes the formula in (24) undefined. We have thus proved the following theorem.

Theorem 3.1. *Let D and Ω be open, bounded sets in $\mathbb{R}^d$ ($d = 2$ or 3) such that $D \subset \Omega$ and $\partial D, \partial\Omega$ are smooth. Suppose $\mathbb{R}^d$ is filled with a material described by the local elasticity tensor given by (10) and (9). Also suppose $\mathbf{f} = \nabla g$ is given and $\mathcal{L}_2 \mathbf{f} = -(\lambda_2 + \mu)\nabla(\nabla \cdot \mathbf{f}) - \mu\Delta \mathbf{f} = 0$ ($\Leftrightarrow \Delta g = C_g \neq 0$) for all $\mathbf{x} \in \mathbb{R}^d$. Assume that $\mathbf{u} \cdot \mathbf{n}_\Omega$ is known around $\partial\Omega$. Then the volume fraction of the inclusion D is given by (24).*

4. Finite Medium

Consider again the linear elasticity problem from Section 3, namely that of an inclusion D in a body Ω which in turn is embedded in an infinite medium $\mathbb{R}^d \setminus \overline{\Omega}$. The isotropic and homogeneous materials in D and $\mathbb{R}^d \setminus \overline{D}$ have Lamé moduli λ_1 and λ_2 , respectively; we also assume that both materials have the same shear modulus μ . If a displacement $\mathbf{f} = \nabla g$ is applied at infinity, then the displacement $\mathbf{u} = \nabla \phi$ satisfies (12) (so ϕ satisfies (17)). Recall that we require $\mathcal{L}_2 \mathbf{f} = 0$ in $\mathbb{R}^d$, which implies $\Delta g = C_g$ in $\mathbb{R}^d$. Since g and $\mathbf{f} = \nabla g$ are smooth in $\mathbb{R}^d$, g , $\mathbf{f}$, and $\mathcal{S}_2 \mathbf{f}$ are continuous up to ∂D from outside D ; in other words, the limits $g|_{\partial D^+}$, $\mathbf{f}|_{\partial D^+}$, and $(\mathcal{S}_2 \mathbf{f})|_{\partial D^+}$ exist and are finite at each point of ∂D , where $h|_{\partial D^+}$ and $h|_{\partial D^-}$ denote the restriction of the function h to ∂D from outside and inside D , respectively.

We now derive a boundary condition $\mathbf{P}$ so that the solution $\mathbf{u}'$ to

$$\begin{cases} \mathcal{L}_1 \mathbf{u}' = 0 & \text{for } \mathbf{x} \in D, \\ \mathcal{L}_2 \mathbf{u}' = 0 & \text{for } \mathbf{x} \in \Omega \setminus \overline{D}, \\ \mathbf{u}', \boldsymbol{\sigma}' \cdot \mathbf{n}_D = (\mathcal{S} \mathbf{u}') \cdot \mathbf{n}_D & \text{continuous across } \partial D, \\ \mathbf{P}(\mathbf{u}'_0, \mathbf{t}'_0, \mathbf{f}_0, \mathbf{F}_0) = 0 & \text{on } \partial\Omega \end{cases} \quad (25)$$

is equal to the solution $\mathbf{u}$ to (12) restricted to $\overline{\Omega}$, i.e., $\mathbf{u}' = \mathbf{u}|_{\overline{\Omega}}$; we have defined

$$\mathbf{u}'_0 \equiv \mathbf{u}'|_{\partial\Omega^-}, \quad \mathbf{t}'_0 \equiv (\boldsymbol{\sigma}'|_{\partial\Omega^-}) \cdot \mathbf{n}_\Omega, \quad \mathbf{f}_0 \equiv \mathbf{f}|_{\partial\Omega^+}, \quad \text{and} \quad \mathbf{F}_0 \equiv [(\mathcal{S}_2 \mathbf{f})|_{\partial\Omega^+}] \cdot \mathbf{n}_\Omega. \quad (26)$$

This allows us to apply our formula (24) to the problem (25), which is posed on the finite domain Ω . For details on a related problem (including proofs of the well-posedness of problems similar to (25)), see the papers of Han and Wu [38, 39].

To derive the boundary condition $\mathbf{P}$, we begin by considering the following exterior problem:

$$\begin{cases} \mathcal{L}_E \tilde{\mathbf{u}}_E = 0 & \text{for } \mathbf{x} \in \mathbb{R}^d \setminus \overline{\Omega}, \\ \tilde{\mathbf{u}}_E = \tilde{\mathbf{u}} & \text{on } \partial\Omega, \\ \tilde{\mathbf{u}}_E \rightarrow 0 & \text{as } |\mathbf{x}| \rightarrow \infty, \end{cases} \quad (27)$$

where $\mathcal{L}_E \mathbf{u} = -(\lambda_E + \mu)\nabla(\nabla \cdot \mathbf{u}) - \mu\Delta \mathbf{u}$, $\lambda_E = \lambda_2$, and $\tilde{\mathbf{u}}$ is a given displacement on $\partial\Omega$. Ultimately we wish to find the normal stress distribution $(\tilde{\boldsymbol{\sigma}}_E|_{\partial\Omega^+}) \cdot \mathbf{n}_\Omega$ around $\partial\Omega$ given $\tilde{\mathbf{u}}$ — this mapping from the displacement on the boundary to the traction on the boundary is defined as the exterior Dirichlet-to-Neumann map.

Definition 4.1. The *exterior Dirichlet-to-Neumann (DtN) map* Λ_E is defined by

$$\Lambda_E(\tilde{\mathbf{u}}_E|_{\partial\Omega^+}) = \Lambda_E(\tilde{\mathbf{u}}) \equiv (\tilde{\boldsymbol{\sigma}}_E|_{\partial\Omega^+}) \cdot \mathbf{n}_\Omega = [(\mathcal{S}\tilde{\mathbf{u}}_E)|_{\partial\Omega^+}] \cdot \mathbf{n}_\Omega, \quad (28)$$

where $\tilde{\mathbf{u}}_E$ solves (27) and $\tilde{\boldsymbol{\sigma}}_E$ and $\mathcal{S}\tilde{\mathbf{u}}_E$ are given by (5) (with $\lambda(\mathbf{x}) = \lambda_E$).

4.1. Equivalent Boundary Value Problems

We now return to the problem (12), which has a unique solution $\mathbf{u}$. We introduce exterior fields

$$\mathbf{u}_E(\mathbf{x}) \equiv \mathbf{u}|_{\mathbb{R}^d \setminus \Omega} \quad \text{and} \quad \boldsymbol{\sigma}_E(\mathbf{x}) \equiv \boldsymbol{\sigma}|_{\mathbb{R}^d \setminus \Omega}; \quad (29)$$

we also introduce interior fields

$$\mathbf{u}_I(\mathbf{x}) \equiv \mathbf{u}|_{\overline{\Omega}} \quad \text{and} \quad \boldsymbol{\sigma}_I(\mathbf{x}) \equiv \boldsymbol{\sigma}|_{\overline{\Omega}}. \quad (30)$$

Recall that $\lambda_E = \lambda_2$.

Lemma 4.2. Define $\tilde{\mathbf{u}}_E \equiv \mathbf{u}_E - \mathbf{f}$ where $\mathbf{u}_E$ is defined in (29) and $\mathbf{f} = \nabla g$ satisfies $\mathcal{L}_E \mathbf{f} = 0$ in $\mathbb{R}^d$. Then $\tilde{\mathbf{u}}_E$ solves (27) with $\tilde{\mathbf{u}} = (\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}_0$, where $\mathbf{f}_0 = \mathbf{f}|_{\partial\Omega^+}$ is defined in (26).

Proof. First, since $\mathcal{L}_E \mathbf{u}_E = 0$ in $\mathbb{R}^d \setminus \overline{\Omega}$ (by (12)) and $\mathcal{L}_E \mathbf{f} = 0$ in $\mathbb{R}^d \setminus \overline{\Omega}$, we have

$$\mathcal{L}_E \tilde{\mathbf{u}}_E = \mathcal{L}_E(\mathbf{u}_E - \mathbf{f}) = \mathcal{L}_E \mathbf{u}_E - \mathcal{L}_E \mathbf{f} = 0$$

in $\mathbb{R}^d \setminus \overline{\Omega}$ as well. Second, recall from (27) that $\tilde{\mathbf{u}} \equiv \tilde{\mathbf{u}}_E|_{\partial\Omega^+} \equiv (\mathbf{u}_E|_{\partial\Omega^+}) - \mathbf{f}_0$. Since $\lambda_E = \lambda_2$, $\mathbf{u}$ must be continuous across $\partial\Omega$, i.e., $\mathbf{u}_E|_{\partial\Omega^+} = \mathbf{u}_I|_{\partial\Omega^-}$. Hence $\tilde{\mathbf{u}} = (\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}_0$. Finally, $\tilde{\mathbf{u}}_E = \mathbf{u}_E - \mathbf{f} \rightarrow 0$ as $|\mathbf{x}| \rightarrow \infty$ by (12). Thus $\tilde{\mathbf{u}}_E$ solves (27) with $\tilde{\mathbf{u}} = (\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}_0$. $\square$

Theorem 4.3. Suppose $\mathbf{u}$ solves (12) with $\mathbf{f} = \nabla g$ and $g = (C_g/2)\mathbf{x} \cdot \mathbf{x} + g_h$ where $C_g \neq 0$ is an arbitrary constant and $\Delta g_h = 0$ in $\mathbb{R}^d$. Define $\mathbf{u}_E$, $\boldsymbol{\sigma}_E$ and $\mathbf{u}_I$, $\boldsymbol{\sigma}_I$ as in (29) and (30), respectively. Finally, define $\tilde{\mathbf{u}}_E = \mathbf{u}_E - \mathbf{f}$. Then $\mathbf{u}_I$ satisfies

$$\begin{cases} \mathcal{L}_1 \mathbf{u}_I = 0 & \text{in } D, \\ \mathcal{L}_2 \mathbf{u}_I = 0 & \text{in } \Omega \setminus \overline{D}, \\ \mathbf{u}_I, \boldsymbol{\sigma}_I \cdot \mathbf{n}_D = (\mathcal{S}\mathbf{u}_I) \cdot \mathbf{n}_D & \text{continuous across } \partial D, \\ \mathbf{P}(\mathbf{u}_I|_{\partial\Omega^-}, (\boldsymbol{\sigma}_I|_{\partial\Omega^-}) \cdot \mathbf{n}_\Omega, \mathbf{f}_0, \mathbf{F}_0) = 0 & \text{on } \partial\Omega, \end{cases} \quad (31)$$

where

$$\mathbf{P}(\mathbf{u}_I|_{\partial\Omega^-}, (\boldsymbol{\sigma}_I|_{\partial\Omega^-}) \cdot \mathbf{n}_\Omega, \mathbf{f}_0, \mathbf{F}_0) \equiv (\boldsymbol{\sigma}_I|_{\partial\Omega^-}) \cdot \mathbf{n}_\Omega - \Lambda_E((\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}_0) - \mathbf{F}_0 \quad (32)$$

and $\mathbf{f}_0$ and $\mathbf{F}_0$ are defined in (26).

Proof. By definition (see (12) and (30)), $\mathbf{u}_I$ satisfies the differential equations and continuity conditions in (31). By Lemma 4.2, $\tilde{\mathbf{u}}_E = \mathbf{u}_E - \mathbf{f}$ solves (27) with $\tilde{\mathbf{u}} = (\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}|_{\partial\Omega^+}$. By (28), then, we have

$$(\tilde{\boldsymbol{\sigma}}_E|_{\partial\Omega^+}) \cdot \mathbf{n}_\Omega = \Lambda_E(\tilde{\mathbf{u}}) = \Lambda_E((\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}_0). \quad (33)$$

Since $\mathcal{S}_E$ is linear, we have

$$(\tilde{\boldsymbol{\sigma}}_E|_{\partial\Omega^+}) \cdot \mathbf{n}_\Omega = [(\mathcal{S}_E \tilde{\mathbf{u}}_E)|_{\partial\Omega^+}] \cdot \mathbf{n}_\Omega = [(\mathcal{S}_E \mathbf{u}_E)|_{\partial\Omega^+}] \cdot \mathbf{n}_\Omega - \mathbf{F}_0. \quad (34)$$

Then (33) and (34) imply

$$[(\mathcal{S}_E \mathbf{u}_E)|_{\partial\Omega^+}] \cdot \mathbf{n}_\Omega = \Lambda_E((\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}_0) + \mathbf{F}_0. \quad (35)$$

Since $\lambda_E = \lambda_2$, the traction across $\partial\Omega$ must be continuous, i.e.,

$$[(\mathcal{S}_E \mathbf{u}_E)|_{\partial\Omega^+}] \cdot \mathbf{n}_\Omega = (\boldsymbol{\sigma}_E|_{\partial\Omega^+}) \cdot \mathbf{n}_\Omega = (\boldsymbol{\sigma}_I|_{\partial\Omega^-}) \cdot \mathbf{n}_\Omega.$$

Inserting this into (35) gives

$$\Lambda_E((\mathbf{u}_I|_{\partial\Omega^-}) - \mathbf{f}_0) + \mathbf{F}_0 = (\boldsymbol{\sigma}_I|_{\partial\Omega^-}) \cdot \mathbf{n}_\Omega. \quad (36)$$

We define $\mathbf{P}(\mathbf{u}_I|_{\partial\Omega^-}, (\boldsymbol{\sigma}_I|_{\partial\Omega^-}) \cdot \mathbf{n}_\Omega, \mathbf{f}_0, \mathbf{F}_0)$ as in (32). Then, due to (36), the interior part of the solution $\mathbf{u}$, namely $\mathbf{u}_I$, satisfies (31). $\square$

We can thus identify the solution $\mathbf{u}'$ of (25) with $\mathbf{u}_I$ which solves (31), i.e., $\mathbf{u}' = \mathbf{u}_I = \mathbf{u}|_{\overline{\Omega}}$. In other words, the solution to (25) in the finite domain Ω will be exactly the same as if Ω were placed in an infinite medium with Lamé parameters $\lambda_E = \lambda_2$ and μ and a displacement ∇g were applied at infinity. Therefore, if we apply the boundary condition

$$\mathbf{P}(\mathbf{u}'_0, \mathbf{t}'_0, \mathbf{f}_0, \mathbf{F}_0) = \mathbf{t}'_0 - \Lambda_E(\mathbf{u}'_0 - \mathbf{f}_0) - \mathbf{F}_0 = 0 \quad (37)$$

on $\partial\Omega$, where $\mathbf{u}'_0$, $\mathbf{t}'_0$, $\mathbf{f}_0$, and $\mathbf{F}_0$ are defined in (26), we can use the measurement of $\mathbf{u}' \cdot \mathbf{n}_\Omega$ around $\partial\Omega$ (i.e., $\mathbf{u}'_0 \cdot \mathbf{n}_\Omega$) along with (24) (with $\mathbf{u}$ replaced by $\mathbf{u}'$) to find the volume fraction occupied by D .

Remark 4.4. Since the geometry inside the body Ω is unknown, we cannot write $\boldsymbol{\sigma}' \cdot \mathbf{n}_\Omega$ in terms of $\mathbf{u}'$ (since we would not know whether or not to use λ_1 or λ_2 in (5)). Practically, we would typically apply a displacement $\mathbf{u}'_0$ around $\partial\Omega$ with a known $\mathbf{f}$ and measure the resulting traction $\mathbf{t}'_0$ around $\partial\Omega$. The displacement $\mathbf{u}'_0$ and traction $\mathbf{t}'_0$ around $\partial\Omega$ must be tailored so that $\mathbf{P}(\mathbf{u}'_0, \mathbf{t}'_0, \mathbf{f}_0, \mathbf{F}_0) = 0$ — see (37).

5. Two Dimensional Example

The results presented here were first derived in a slightly different form by Han and Wu [38, 39]. We consider the case when $d = 2$ and Ω is a disk of radius R centered at the origin, denoted B_R . In this geometry, it is possible to determine Λ_E exactly by first solving (27) for the displacement $\tilde{\mathbf{u}}_E$ in terms of $\tilde{\mathbf{u}} = \tilde{\mathbf{u}}_E|_{\partial B_R}$ and then computing the corresponding traction around ∂B_R , namely

$$(\tilde{\boldsymbol{\sigma}}_E|_{\partial B_R^+}) \cdot \mathbf{n}_{B_R} = \left(\tilde{\boldsymbol{\sigma}}_E \cdot \frac{\mathbf{x}}{R} \right) \Big|_{\partial B_R^+} = \left[\mathcal{S}_E(\tilde{\mathbf{u}}_E) \cdot \frac{\mathbf{x}}{R} \right] \Big|_{\partial B_R^+}.$$

We state the main results here; the complete calculations are given in work by one of the authors [23]. For more general regions, Λ_E may have to be computed numerically.

5.1. Exterior Dirichlet-to-Neumann Map

We denote the polar components of $\tilde{\mathbf{u}}_E$ by $\tilde{u}_{E,r}$ and $\tilde{u}_{E,\theta}$. It is convenient to write

$$\tilde{\mathbf{u}}_E(r, \theta) = \tilde{u}_{E,r}(r, \theta) + i\tilde{u}_{E,\theta}(r, \theta),$$

where $i = \sqrt{-1}$; see the books by Muskhelishvili [45] and England [46] for more details.

We begin by expanding $\tilde{\mathbf{u}}(\theta) = \tilde{u}_r(\theta) + i\tilde{u}_\theta(\theta)$ in a Fourier series, namely

$$\tilde{u}_r(\theta) + i\tilde{u}_\theta(\theta) = \sum_{n=-\infty}^{\infty} \tilde{u}_n e^{in\theta}, \quad \text{where} \quad \tilde{u}_n = \frac{1}{2\pi} \int_0^{2\pi} [\tilde{u}_r(\theta') + i\tilde{u}_\theta(\theta')] e^{-in\theta'} d\theta'. \quad (38)$$

Then it can be shown that [23]

$$\begin{aligned} \tilde{u}_{E,r}(r, \theta) + i\tilde{u}_{E,\theta}(r, \theta) &= \tilde{u}_0 R r^{-1} + \sum_{n=1}^{\infty} \tilde{u}_{-n} R^{n-1} r^{-(n-1)} e^{-in\theta} \\ &\quad + \sum_{n=1}^{\infty} \left[\tilde{u}_n R^{n+1} r^{-(n+1)} + \left(\frac{n-1}{\rho_E} \right) \overline{\tilde{u}_{-n}} R^{n-1} r^{-(n+1)} (r^2 - R^2) \right] e^{in\theta} \end{aligned} \quad (39)$$

for $r \geq R$ and where $\rho_E \equiv (\lambda_E + 3\mu)/(\lambda + \mu)$.

Next we recall from (28) that $\Lambda_E(\tilde{\mathbf{u}}) = (\tilde{\boldsymbol{\sigma}}_E|_{\partial B_R^+}) \cdot \mathbf{n}_{B_R}$. In polar coordinates, the components of the traction around the boundary of the disk of radius $r \geq R$ are $\tilde{\sigma}_{E,rr}(r, \theta) + i\tilde{\sigma}_{E,r\theta}(r, \theta)$ (where $\tilde{\sigma}_{E,rr}$ is the radial component of the traction and $\tilde{\sigma}_{E,r\theta}$ is the angular component of the traction). In particular, the traction around ∂B_R is given by

$$\tilde{\sigma}_{E,rr}(R^+, \theta) + i\tilde{\sigma}_{E,r\theta}(R^+, \theta) = \Lambda_E(\tilde{\mathbf{u}}) = \sum_{n=-\infty}^{\infty} \tilde{\sigma}_n e^{in\theta}, \quad (40)$$

where $\tilde{\sigma}_{E,rr}(R^+, \theta) + i\tilde{\sigma}_{E,r\theta}(R^+, \theta) = (\tilde{\sigma}_{E,rr} + i\tilde{\sigma}_{E,r\theta})|_{\partial B_R^+}$,

$$\begin{cases} \tilde{\sigma}_n = -\frac{2\mu}{R}(n+1)\tilde{u}_n & (n \geq 0), \\ \tilde{\sigma}_{-n} = -\frac{2\mu}{R\rho_E}(n-1)\tilde{u}_{-n} & (n \geq 1), \end{cases} \quad (41)$$

and the coefficients $\tilde{u}_n$ are defined in (38).

5.2. Nonlocal Boundary Condition

In this section, we derive an expression for the boundary condition $\mathbf{P}(\mathbf{u}'_0, \mathbf{t}'_0, \mathbf{f}_0, \mathbf{F}_0) = 0$, where $\mathbf{P}$ is defined in (37). We begin by expanding $\mathbf{f}_0$ in a Fourier series around ∂B_R ; we have

$$(f_r + if_\theta)|_{\partial B_R^+} = f_r(R^+, \theta) + if_\theta(R^+, \theta) = f_{0,r}(\theta) + if_{0,\theta}(\theta) = \sum_{n=-\infty}^{\infty} f_{0,n} e^{in\theta}, \quad (42)$$

where

$$f_{0,n} = \frac{1}{2\pi} \int_0^{2\pi} [f_{0,r}(\theta') + if_{0,\theta}(\theta')] e^{-in\theta'} d\theta'.$$

Next we define

$$\mathbf{F} \equiv \mathcal{S}_E \mathbf{f} = \mathcal{S}_E \nabla g = \lambda_E \Delta g \mathbf{I} + 2\mu \nabla \nabla g,$$

where the last equality holds by (11). Recall from (26) that $\mathbf{F}_0 = (\mathbf{F}|_{\partial B_R^+}) \cdot \mathbf{n}_{B_R}$. In complex notation, the normal components of $\mathbf{F}$ around the boundary of a disk of radius $r > 0$ are given by $F_{rr}(r, \theta) + iF_{r\theta}(r, \theta)$, where F_{rr} is the radial component and $F_{r\theta}$ is the angular component. We can expand $(F_{rr} + iF_{r\theta})|_{\partial B_R^+}$ in a Fourier series as

$$(F_{rr} + iF_{r\theta})|_{\partial B_R^+} = F_{rr}(R^+, \theta) + iF_{r\theta}(R^+, \theta) = F_{0,r}(\theta) + iF_{0,\theta}(\theta) = \sum_{n=-\infty}^{\infty} F_{0,n} e^{in\theta}, \quad (43)$$

where

$$F_{0,n} = \frac{1}{2\pi} \int_0^{2\pi} [F_{0,r}(\theta') + iF_{0,\theta}(\theta')] e^{-in\theta'} d\theta'.$$

Next we expand g in a Fourier series around the disk of radius $r > 0$ as

$$g(r, \theta) = \sum_{n=-\infty}^{\infty} g_n(r) e^{in\theta}, \quad \text{where} \quad g_n(r) = \frac{1}{2\pi} \int_0^{2\pi} g(r, \theta') e^{-in\theta'} d\theta'.$$

We can write the Fourier coefficients $F_{0,n}$ in terms of the coefficients g_n as

$$\begin{aligned} F_{0,n} = & (\lambda_E + 2\mu) \left. \frac{\partial^2 g_n(r)}{\partial r^2} \right|_{r \rightarrow R^+} + \lambda_E \left[\frac{1}{R} \left. \frac{\partial g_n(r)}{\partial r} \right|_{r \rightarrow R^+} - \frac{n^2}{R^2} g_n(R^+) \right] \\ & + 2\mu \left[-\frac{n}{R} \left. \frac{\partial g_n(r)}{\partial r} \right|_{r \rightarrow R^+} + \frac{n}{R^2} g_n(R^+) \right]. \end{aligned} \quad (44)$$

Returning to (32), recall that $(\mathbf{u}'|_{\partial B_R^-}) - \mathbf{f}|_{\partial B_R^+} = \mathbf{u}'_0 - \mathbf{f}_0 = \tilde{\mathbf{u}}$, where $\mathbf{u}'$ solves (25). Thus if we write

$$(u'_r + iu'_\theta)|_{\partial B_R^-} = u'_r(R^-, \theta) + iu'_\theta(R^-, \theta) = u'_{0,r}(\theta) + iu'_{0,\theta}(\theta) = \sum_{n=-\infty}^{\infty} u'_{0,n} e^{in\theta},$$

where

$$u'_{0,n} = \frac{1}{2\pi} \int_0^{2\pi} [u'_{0,r}(\theta') + iu'_{0,\theta}(\theta')] e^{in\theta'} d\theta',$$

then $u'_{0,n} - f_{0,n} = \tilde{u}_n$ — see (38). The components of the traction $(\boldsymbol{\sigma}'|_{\partial B_R^-}) \cdot \mathbf{n}_{B_R} = \mathbf{t}'_0$ can be written in polar coordinates as $t'_{0,r}(\theta) + it'_{0,\theta}(\theta)$. This can be expanded in a Fourier series as well, namely

$$(\sigma'_{rr} + i\sigma'_{r\theta})|_{\partial B_R^-} = \sigma'_{rr}(R^-, \theta) + i\sigma'_{r\theta}(R^-, \theta) = t'_{0,r}(\theta) + it'_{0,\theta}(\theta) = \sum_{n=-\infty}^{\infty} t'_{0,n} e^{in\theta},$$

where

$$t'_{0,n} = \frac{1}{2\pi} \int_0^{2\pi} [t'_{0,r}(\theta') + it'_{0,\theta}(\theta')] e^{-in\theta'} d\theta'.$$

Recalling the Fourier expansions of $\mathbf{f}_0$ given in (42), $\mathbf{F}_0$ given in (43) (and (44)), and $\Lambda_E(\tilde{\mathbf{u}}) = \Lambda_E(\mathbf{u}'_0 - \mathbf{f}_0)$ given in (40)–(41), the condition $\mathbf{P}(\mathbf{u}'_0, \mathbf{t}'_0, \mathbf{f}_0, \mathbf{F}_0) = 0$ is equivalent to

$$\begin{aligned} \mathbf{t}'_0 - \mathbf{F}_0 - \Lambda_E(\mathbf{u}'_0 - \mathbf{f}_0) &= 0 \\ \Leftrightarrow \sum_{n=-1}^{\infty} \left[t'_{0,n} - F_{0,n} + \frac{2\mu}{R}(n+1)(u'_{0,n} - f_{0,n}) \right] e^{in\theta} \\ &+ \sum_{n=2}^{\infty} \left[t'_{0,-n} - F_{0,-n} + \frac{2\mu}{R\rho_E}(n-1)(u'_{-n} - f_{0,-n}) \right] e^{-in\theta} = 0. \end{aligned} \quad (45)$$

Therefore we have the following relationships between the Fourier coefficients of the polar components of the displacement, traction, and applied stress around ∂B_R :

$$\begin{cases} t'_{0,n} - F_{0,n} + \frac{2\mu}{R}(n+1)(u'_{0,n} - f_{0,n}) = 0 & (n \geq -1), \\ t'_{0,-n} - F_{0,-n} + \frac{2\mu}{R\rho_E}(n-1)(u'_{-n} - f_{0,-n}) = 0 & (n \geq 2). \end{cases} \quad (46)$$

Remark 5.1. Recall from (25) that $\mathbf{t}'_0$ is the traction around ∂B_R due to the applied displacement $\mathbf{u}'_0$. In practice, one could consider applying a displacement $\mathbf{u}'_0$ around $\partial\Omega$ with a known $\mathbf{f}$ and then measuring $\mathbf{t}'_0$ around ∂B_R . The applied displacement $\mathbf{u}'_0$ and measured traction $\mathbf{t}'_0$ have to be such that (45) (and, hence, (46)) holds.

5.3. Previous Results

Previously, Han and Wu also derived an expression for the exterior DtN map $\Lambda_E(\tilde{\mathbf{u}})$ [38, 39]. They found the solution $\tilde{\mathbf{u}}_E$ to (27) by a method slightly different from the one we used; they then computed the Cartesian components of the traction $\tilde{\boldsymbol{\sigma}}_E \cdot \mathbf{n}_\Omega$ around ∂B_R . In particular, if we denote the Cartesian components of $\tilde{\mathbf{u}}_E$ by $\tilde{u}_E$ and $\tilde{v}_E$, the Cartesian components of $\tilde{\mathbf{u}}_E|_{\partial B_R^+} = \tilde{\mathbf{u}}$ by $\tilde{u}$ and $\tilde{v}$, and the Cartesian components of the traction $(\tilde{\boldsymbol{\sigma}}_E|_{\partial B_R^+}) \cdot \mathbf{n}_{B_R}$ by $\tilde{X}$ and $\tilde{Y}$, then $\Lambda_E(\tilde{\mathbf{u}}) = \Lambda_E(\tilde{u} + i\tilde{v}) = \tilde{X} + i\tilde{Y}$. In particular

they showed [39, equations (29) and (30)]

$$\begin{aligned}
\tilde{X} &= \frac{2+2\eta}{1+2\eta} \frac{\mu}{\pi R} \sum_{n=1}^{\infty} \int_0^{2\pi} \frac{d^2 \tilde{u}(\theta')}{d\theta'^2} \frac{\cos n(\theta - \theta')}{n} d\theta' \\
&\quad - \frac{2\eta}{1+2\eta} \frac{\mu}{\pi R} \sum_{n=1}^{\infty} \int_0^{2\pi} \frac{d^2 \tilde{v}(\theta')}{d\theta'^2} \frac{\sin n(\theta - \theta')}{n} d\theta'; \\
\tilde{Y} &= \frac{2+2\eta}{1+2\eta} \frac{\mu}{\pi R} \sum_{n=1}^{\infty} \int_0^{2\pi} \frac{d^2 \tilde{v}(\theta')}{d\theta'^2} \frac{\cos n(\theta - \theta')}{n} d\theta' \\
&\quad + \frac{2\eta}{1+2\eta} \frac{\mu}{\pi R} \sum_{n=1}^{\infty} \int_0^{2\pi} \frac{d^2 \tilde{u}(\theta')}{d\theta'^2} \frac{\sin n(\theta - \theta')}{n} d\theta'
\end{aligned} \tag{47}$$

where $\tilde{u}(\theta') = \tilde{u}_E(R^+, \theta')$, $\tilde{v}(\theta') = \tilde{v}_E(R^+, \theta')$, and $\eta = \mu/(\lambda_E + \mu)$. Also see the books by Muskhelishvili [45, Section 83] and England [46, Section 4.2] for solutions to problems related to (27) based on potential formulations. A proof that our formulas (40)–(41) agree with (47) as long as $\tilde{\mathbf{u}}$ is smooth enough is given in the work by Thaler [23].

Acknowledgments

AET would like to thank Patrick Bardsley, Andrej Cherkaev, Elena Cherkaev, Fernando Guevara Vasquez, and Hyeonbae Kang for helpful discussions. The work of AET and GWM was supported by the National Science Foundation through grant DMS-1211359.

References

- [1] R. C. McPhedran, D. R. McKenzie, and G. W. Milton. Extraction of structural information from measured transport properties of composites. *Applied Physics A*, 29:19–27, 1982.
- [2] N. Phan-Thien and G. W. Milton. A possible use of bounds on effective moduli of composite materials. *Journal of Reinforced Plastics and Composites*, 1:107–114, 1982.
- [3] R. C. McPhedran and G. W. Milton. Inverse transport problems for composite media. *Materials Research Society Symposium Proceedings*, 195:257–274, 1990.
- [4] H. Kang, J. K. Seo, and D. Sheen. The inverse conductivity problem with one measurement: stability and estimation of size. *SIAM Journal on Mathematical Analysis*, 28(6):1389–1405, 1997.
- [5] G. Alessandrini and E. Rosset. The inverse conductivity problem with one measurement: bounds on the size of the unknown object. *SIAM Journal on Applied Mathematics*, 58(4):1060–1071, 1998.
- [6] E. Cherkaeva and K. Golden. Inverse bounds for microstructural parameters of composite media derived from complex permittivity measurements. *Waves in Random Media*, 8(4):437–450, 1998.
- [7] M. Ikehata. Size estimation of inclusion. *Journal of Inverse and Ill-Posed Problems*, 6(2):127–140, 1998.
- [8] G. Alessandrini, E. Rosset, and J. K. Seo. Optimal size estimates for the inverse conductivity problem with one measurement. *Proceedings of the American Mathematical Society*, 128(1):53–64, September 2000.
- [9] G. Alessandrini, A. Morassi, and E. Rosset. Detecting an inclusion in an elastic body by boundary measurements. *SIAM Journal on Mathematical Analysis*, 33(6):1247–1268, 2002.
- [10] G. Alessandrini, A. Morassi, and E. Rosset. Detecting cavities by electrostatic boundary measurements. *Inverse Problems*, 18:1333–1353, 2002.

- [11] Y. Capdeboscq and M. S. Vogelius. Optimal asymptotic estimates for the volume of internal inhomogeneities in terms of multiple boundary measurements. *Mathematical Modelling and Numerical Analysis = Modelisation mathématique et analyse numérique: M²AN*, 37:227–240, 2003.
- [12] G. Alessandrini, A. Morassi, and E. Rosset. Detecting an inclusion in an elastic body by boundary measurements. *SIAM Review*, 46(3):477–498, 2004.
- [13] Y. Capdeboscq and H. Kang. Improved Hashin–Shtrikman bounds for elastic moment tensors and an application. *Applied Mathematics and Optimization*, 57:263–288, 2008.
- [14] A. Morassi, E. Rosset, and S. Vessella. Detecting general inclusions in elastic plates. *Inverse Problems*, 25:045009, 2009.
- [15] E. Beretta, E. Francini, and S. Vessella. Size estimates for the EIT problem with one measurement: the complex case. *Revista Matemática Iberoamericana*, 2011. Also see arxiv:1108.0052v2 [math.AP].
- [16] H. Kang, E. Kim, and G. W. Milton. Sharp bounds on the volume fractions of two materials in a two-dimensional body from electrical boundary measurements: the translation method. *Calculus of Variations and Partial Differential Equations*, 45(3–4):367–401, 2012.
- [17] G. W. Milton and L. H. Nguyen. Bounds on the volume fraction of 2-phase, 2-dimensional elastic bodies and on (stress, strain) pairs in composites. *Comptes Rendus Mécanique*, 340(4–5):193–204, 2012.
- [18] G. W. Milton. Universal bounds on the electrical and elastic response of two-phase bodies and their application to bounding the volume fraction from boundary measurements. *Journal of the Mechanics and Physics of Solids*, 60(1):139–155, 2012.
- [19] H. Kang, K. Kim, H. Lee, X. Li, and G. W. Milton. Bounds on the size of an inclusion using the translation method for two-dimensional complex conductivity. *SIAM Journal on Applied Mathematics*, to appear. Also see arxiv:1310.2439 [math.AP].
- [20] H. Kang and G. W. Milton. Bounds on the volume fractions of two materials in a three dimensional body from boundary measurements by the translation method. *SIAM Journal on Applied Mathematics*, 73:475–492, 2013.
- [21] A. E. Thaler and G. W. Milton. Bounds on the volume of an inclusion in a body from a complex conductivity measurement. *Communications in Mathematical Sciences*, to appear. Also see arxiv:1306.6608 [math.AP].
- [22] H. Kang, G. W. Milton, and J.-N. Wang. Bounds on the volume fraction of the two-phase shallow shell using one measurement. *Journal of Elasticity*, 114(1):41–53, 2014.
- [23] A. E. Thaler. *Bounds on the volume of an inclusion in a body and cloaking due to anomalous localized resonance*. Ph.D. thesis, University of Utah, Salt Lake City, UT, 2014.
- [24] R. Hill. Elastic properties of reinforced solids: Some theoretical principles. *Journal of the Mechanics and Physics of Solids*, 11(5):357–372, 1963.
- [25] Z. Hashin. Analysis of composite materials — A survey. *Journal of Applied Mechanics*, 50(3):481–505, 1983.
- [26] G. W. Milton. *The Theory of Composites*, volume 6 of *Cambridge Monographs on Applied and Computational Mathematics*. Cambridge University Press, Cambridge, United Kingdom, 2002.
- [27] G. J. Dvorak and Y. Benveniste. On micromechanics of inelastic and piezoelectric composites. In T. Tatsumi, E. Watanabe, and T. Kambe, editors, *Theoretical and Applied Mechanics 1996: Proceedings of the XIXth International Congress of Theoretical and Applied Mechanics, Kyoto, Japan, 25–31 August 1996*, pages 217–237, Amsterdam, 1997. Elsevier.
- [28] G. W. Milton. Composites: A myriad of microstructure independent relations. In T. Tatsumi, E. Watanabe, and T. Kambe, editors, *Theoretical and Applied Mechanics 1996: Proceedings of the XIXth International Congress of Theoretical and Applied Mechanics, Kyoto, Japan, 25–31 August 1996*, pages 443–459, Amsterdam, 1997. Elsevier.
- [29] Y. Grabovsky, G. W. Milton, and D. S. Sage. Exact relations for effective tensors of composites: Necessary conditions and sufficient conditions. *Communications on Pure and*

- Applied Mathematics*, 53(3):300–353, 2000.
- [30] M. Hegg. *Exact relations and links for fiber-reinforced elastic composites*. PhD thesis, Temple University, Philadelphia, Pennsylvania, 2012.
 - [31] M. Hegg. Links between effective tensors for fiber-reinforced elastic composites. *Comptes Rendus Mécanique*, 341(6):520–532, 2013.
 - [32] Y. Grabovsky. Exact relations for effective tensors of polycrystals. I. Necessary conditions. *Archive for Rational Mechanics and Analysis*, 143(4):309–329, 1998.
 - [33] Y. Grabovsky and D. S. Sage. Exact relations for effective tensors of polycrystals. II. Applications to elasticity and piezoelectricity. *Archive for Rational Mechanics and Analysis*, 143(4):331–356, 1998.
 - [34] Y. Grabovsky and G. W. Milton. Exact relations for composites: Towards a complete solution. *Documenta Mathematica, Journal der Deutschen Mathematiker-Vereinigung*, Extra Volume ICM III:623–632, 1998.
 - [35] Y. Grabovsky and G. W. Milton. Rank one plus a null-Lagrangian is an inherited property of two-dimensional compliance tensors under homogenization. *Proceedings of the Royal Society of Edinburgh*, 128A(2):283–299, 1998.
 - [36] R. Hill. Theory of mechanical properties of fibre-strengthened materials: I. Elastic behaviour. *Journal of the Mechanics and Physics of Solids*, 12(4):199–212, 1964.
 - [37] D. Givoli. Non-reflecting boundary conditions. *Journal of Computational Physics*, 94(1):1–29, 1991.
 - [38] H. Han and X. Wu. Approximation of infinite boundary condition and its application to finite element methods. *Journal of Computational Mathematics*, 3(2):179–192, 1985.
 - [39] H. Han and X. Wu. The approximation of the exact boundary conditions at an artificial boundary for linear elastic equations and its application. *Mathematics of Computation*, 59(199):21–37, 1992.
 - [40] S. Lee, R. E. Caflisch, and Y.-J. Lee. Exact artificial boundary conditions for continuum and discrete elasticity. *SIAM Journal on Applied Mathematics*, 66(5):1749–1775, 2006.
 - [41] V. Bonnaillie-Noël, M. Dambrine, F. Hérau, and G. Vial. Artificial conditions for the linear elasticity equations. *Mathematics of Computation*, to appear.
 - [42] H. Ammari and H. Kang. *Polarization and Moment Tensors With Applications to Inverse Problems and Effective Medium Theory*, volume 162 of *Applied Mathematical Sciences*. Springer, New York, 2007.
 - [43] R. Hill. Discontinuity relations in mechanics of solids. In I. N. Sneddon and R. Hill, editors, *Progress in Solid Mechanics*, volume II, chapter VI, pages 247–276. North-Holland Publishing Co., Amsterdam, 1961.
 - [44] L. C. Evans. *Partial Differential Equations*, volume 19 of *Graduate Studies in Mathematics*. American Mathematical Society, Providence, 2010.
 - [45] N. I. Muskhelishvili. *Some Basic Problems of the Mathematical Theory of Elasticity: Fundamental Equations, Plane Theory of Elasticity, Torsion, and Bending*. P. Noordhoff, Groningen, The Netherlands, 1963.
 - [46] A. H. England. *Complex Variable Methods in Elasticity*. Wiley-Interscience, New York, 1971.